

SAI "Basic 850" de 850 VA, tomas de salida Shuko, negro

EG-UPS-B850

ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Características

- Fuente de alimentación ininterrumpida de 850 VA para PC
- Regulación automática de voltaje de salida (AVR)
- Indicación de estado LED
- Protección contra cortocircuitos
- Protección contra sobretensiones, picos y rayos.
- Alarmas sonoras y visuales
- Protección de sobrecarga y sobredescarga

Embalaje

Cantidad por caja, pcs	4
Volumen caja, M3	0,045356
Peso caja, kgs	21.4
Medidas cajas individuales LxWxH:	338x147x210 mm
Medidas caja LxWxH	580x340x230 mm
Pais de origen	CN
Código de barras	8716309087070
codigo de aduanas	8504408590

Contenido de la caja

- UPS
- User manual

Especificaciones

UPS type: line interactive
 Input: AC 220V±25%, 50Hz/60Hz ±10%
 Output: AC 220V±10%, 50Hz/60Hz ±0.5% (on battery)
 Switching time: 4-8ms
 Backup time: up to .20 mins (depends on the load)
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12V/8Ah x 1 pc

Charge time: up to 12 hours
 Sockets: 2 x Schuko output (CEE 7/4)
 Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing
 Power: 850 VA (510 W)

Requisitos del sistema

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Certificados

